



Web: www.sizonkegroup.co.za

- **Water based degreaser**
- **Effective for removal of oil and greases**

Sizonke WBD is a combination penetrant, sequesterant and wetting agent.

Sizonke WBD is a heavy duty cleaner containing a quick penetrating component for efficient oil, grease and dirt removal. Sizonke WBD has high emulsification powers that will enable quick and efficient cleaning of equipment, motors and machinery, and for hard surface, floor cleaning as in garages and engineering workshops.

Product Characteristics

AppearanceClear yellow liquid

pH..... 11,5 – 12,5

Density @ 25°C.....1,02 – 1,04 g/m³l

Solubility in waterSoluble in water

Approx. Volume per kg971 m³l

Methods of Application

Based on the system operating conditions, your Sizonke representative will recommend the optimum dosage level and the most suitable point of application for the product.

Sizonke WBD can be applied neat to the area to be cleaned by means of sprays, brushes or immerse the article in a bath of cleaning liquid. After a short soaking period, it can be rinsed off with water. For hard surface floor cleaning, Sizonke WBD should be brushed into the soiled area with a firm brush and allowed to soak for several minutes, about 10 – 20 minutes depending on the amount of contamination to be removed. After this period, the area should be sluiced and brushed with fresh water, which removes the detergent and emulsified oil and greases. If the contamination is very heavy and has been present for some time, it might be found necessary to repeat the procedure.

Packaging, Handling and Storage

Sizonke WBD is available in 20l non-returnable drums or in bulk deliveries. Materials of construction suitable for handling and storing the product are penton, teflon, stainless steel, polypropylene and polyethylene.

The containers should be kept closed when not in use. Sizonke WBD should be stored under normal warehouse conditions. The recommended shelf-life is 12 months from the time of despatch. The stock must be rotated on a first in, first out basis to minimise storage time.

Improper handling of the product can be injurious to workers. Observe all safety precautions listed on the label and in the Material Safety Data Sheet.